



Art.-Nr. 4046736

ASCO CO<sub>2</sub> cylinder valve made of brass with:

- O-ring
- Maximum operating pressure 200 bar (2900 psi)
- Inner thread for syphon tube
- Aluminium hand wheel
- Bursting safety disc (bursting pressure 190 bar) (2'755 psi)

## ASCO CO<sub>2</sub> Cylinder Valve

ASCO CO<sub>2</sub> Cylinder Valve are used on standard CO<sub>2</sub> cylinders to regulate the CO<sub>2</sub> supply.

The CO<sub>2</sub> valve consists of an aluminium hand wheel and brass body. The threading is conical for safe and proper sealing.

All ASCO CO<sub>2</sub> Cylinder Valves are equipped with bursting disc for maximum safety.

### Specifications:

A = W 21,8 x 1/14" to DIN 477

B = Ø 8 mm (0.3 in)

C = 28.8 x 1/14"

D = Ø 7 mm (0.3 in)

E = 112 mm (4.4 in)

F = 47 mm (1.9 in)

G = M10 x 0.75 mm

Bursting disc = 190 bar (2756 psi)

Handwheel = Aluminium

Valve Body = Brass

Weight approx. = 520 g (1.45 lb)

Valves to other specifications on request!

